

ADSL Router Login

الدخول لمتصفح google chrome وتسجيل ip
الراوتر بالبحث 192.168.1.

User Name:

Password:

> WAN

> WAN

> Auto PVC

> ATM

> ADSL


▼ LAN

















▼ WLAN

WAN Configuration

This page is used to configure the parameters for the WAN interface of your ADSL and(or) Ethernet Modem/Router. Note : When connect type of PPPoE and PPPoA only is "Manual", the "Connect" and "Disconnect" button will be enable.

WAN Physical Type:	<input checked="" type="radio"/> ADSL WAN	<input type="radio"/> Ethernet WAN	
Default Route Selection:	<input type="radio"/> Auto	<input checked="" type="radio"/> Specified	
VPI:	<input type="text" value="0"/>	VCI:	<input type="text"/>
Encapsulation:	<input checked="" type="radio"/> LLC	<input type="radio"/> VC-Mux	
Channel Mode:	<input type="text" value="Bridge"/>	Enable NAPT:	<input type="checkbox"/>
Enable IGMP:	<input type="checkbox"/>		
PPP Settings:			
User Name:	<input type="text"/>	Password:	<input type="text"/>
Type:	<input type="text" value="Continuous"/>	Idle Time (min):	<input type="text"/>
WAN IP Settings:			
Type:	<input checked="" type="radio"/> Fixed IP	<input type="radio"/> DHCP	

 WAN Interfaces Table:

Select	Inf	Mode	VPI	VCI	Encap	NAPT	IGMP	DRoute	IP Address	ISP Gateway	Subnet Mask	User Name	Status	Edit
<input checked="" type="radio"/>	2 pppoe 2	PPPoE	0	32	LLC	On	On	Off					up	 
<input type="radio"/>	WAN1	br1483	1	33	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 
<input type="radio"/>	WAN2	br1483	0	35	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 
<input type="radio"/>	WAN3	br1483	0	100	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 
<input type="radio"/>	pppoe 1	PPPoE	8	35	LLC	On	Off	On	10.236.43.2 6	185.158.92. 3	255.255.2 55.255	may.ah mad@w a ves.sy	up	 
<input type="radio"/>	WAN5	br1483	1	50	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 
<input type="radio"/>	WAN6	br1483	8	81	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 
<input type="radio"/>	WAN7	br1483	0	200	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 

[Status](#)[Quick Start](#)[Setup](#)[Advanced](#)[Service](#)[Firewall](#)[Maintenance](#)[WAN](#)[WAN](#)[Auto PVC](#)[ATM](#)[ADSL](#)[LAN](#)[WLAN](#)

WAN Configuration

This page is used to configure the parameters for the WAN interface of your ADSL and(or) Ethernet Modem/Router. Note : When connect type of PPPoE and PPPoA only is "Manual", the "Connect" and "Disconnect" button will be enable.

WAN Physical Type: ADSL WAN Ethernet WANDefault Route Selection: Auto SpecifiedVPI: **3**

VCI:

Encapsulation:

 LLC VC-Mux

Channel Mode:

Enable NAPT:

Enable IGMP:

IP Protocol:

PPP Settings:

7 waves.iptv.sy

****wg

User Name:

Password:

Type:

Idle Time (min):

WAN IP Settings:

Type:

Fixed IP

DHCP

IP Address:

ISP Gateway:

Subnet Mask:

Primary DNS Server:

Secondary DNS Server:

Default Route:

Disable

Enable

Auto

Unnumbered:

9

IPv6 WAN Setting:

Address Mode:

Slaac ▾

IPv6 DNS Mode:

Auto ▾

DHCPv6 Mode:

Auto ▾

Request DHCPv6 PD:

10

Connect

Disconnect
















Add

Modify

Delete

Undo

Refresh

Select	Inf	Mode	VPI	VCI	Encap	NAPT	IGMP	DRoute	IP Address	ISP Gateway	Subnet Mask	User Name	Status	Edit
<input checked="" type="radio"/>	pppoe 2	PPPoE	0	32	LLC	On	On	Off	10.113.103.3	10.10.0.200		11 ---	up	 
<input type="radio"/>	WAN1	br1483	1	33	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 
<input type="radio"/>	WAN2	br1483	0	35	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 
<input type="radio"/>	WAN3	br1483	0	100	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 
<input type="radio"/>	pppoe 1	PPPoE	8	35	LLC	On	Off	On	10.236.43.2 6	185.158.92. 3	255.255.2 55.255	may.ah mad@w a ves.sy	up	 
<input type="radio"/>	WAN5	br1483	1	50	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 
<input type="radio"/>	WAN6	br1483	8	81	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 
<input type="radio"/>	WAN7	br1483	0	200	LLC	Off	Off	Off	0.0.0.0	0.0.0.0	0.0.0.0	---	up	 

ATM VCC:	0/32
Login Name:	<input type="text"/>
Password:	<input type="password"/>
Authentication Method:	AUTO ▾
Connection Type:	Continuous ▾
Idle Time (s):	<input type="text" value="0"/>
Bridge:	<input checked="" type="radio"/> Bridged Ethernet (Transparent Bridging) 12
	<input type="radio"/> Bridged PPPoE (implies Bridged Ethernet)
	<input type="radio"/> Disable Bridge
AC-Name:	<input type="text"/>
Service-Name:	<input type="text"/>

802.1q:	<input checked="" type="radio"/> Disable <input type="radio"/> Enable
VLAN ID(1-4095):	<input type="text" value="0"/>
MTU (1-1500):	<input type="text" value="1492"/>
Static:	<input type="text"/>
Source Mac address:	<input type="text" value="E4:BE:ED:FF:27:B2"/> (ex:00:E0:86:71:05:02) <input type="button" value="MACCLONE"/>

Status

Quick Start

Setup

Advanced

Service

Firewall

Maintenance

14

> Route

> Static Route

> IPv6 Static Route

> RIP

✓ NAT

✓ QoS

✓ CWMP

✓ Port Mapping

✓ Others

Routing Configuration

This page is used to configure the routing information. Here you can add/delete IP routes.

Enable:



Destination:

10.1.0.0

Subnet Mask:

255.255.255.0

Next Hop:

Metric:

1

Interface:

pppoe2 ▾

15

protv

Add Route

Update

Delete Selected

Show Routes

16

Static Route Table:

Select	State	Destination	Subnet Mask	NextHop	Metric	Itf
<input type="radio"/>					1	

14

Status

Quick Start

Setup

Advanced

Service

Firewall

Maintenance

> Route

> Static Route

> IPv6 Static Route

> RIP

✓ NAT

✓ QoS

✓ CWMP

✓ Port Mapping

✓ Others

Routing Configuration

This page is used to configure the routing information. Here you can add/delete IP routes.

Enable:	<input checked="" type="checkbox"/>
Destination:	<input type="text" value="10.237.239.0"/>
Subnet Mask:	<input type="text" value="255.255.255.0"/>
Next Hop:	<input type="text"/>
Metric:	<input type="text" value="1"/>
Interface:	<input type="text" value="pppoe2"/>

15

liketv

16

Add Route

Update

Delete Selected

Show Routes

Static Route Table:

Select	State	Destination	Subnet Mask	NextHop	Metric	Itf
<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>