

الدخول لمتصفح google chrome وتسجيل ip
الراوتر بالبحث 192.168.1.

Username:

Password:

Login

Copyright © 2018 TP-LINK Technologies Co., Ltd. All rights reserved.

Interface | **1 Quick Start** | **Interface Setup** | **Advanced Setup** | **Access Management** | **Maintenance** | **Status** | **Help**

Internet | LAN | Wireless | 6RD | Guest Network

ATM VC

Virtual Circuit : PVC0

Status : Activated Deactivated

3 VPI : 0 (range: 0~255)

4 VCI : 32 (range: 32~65535)

QoS

ATM QoS : UBR

PCR : 0 cells/second

SCR : 0 cells/second

MBS : 0 cells

IPv4/IPv6

IP Version : IPv4 IPv4/IPv6 IPv6

Encapsulation

ISP : Dynamic IP Address
 Static IP Address
5 PPPoA/PPPoE
 Bridge Mode

Bridge Mode

Encapsulation : 1483 Bridged IP LLC

SAVE | DELETE

Interface	Quick Start	Interface Setup	Advanced Setup	Access Management	Maintenance	Status	Help
	Internet	LAN	Wireless	6RD	Guest Network		

- PPPoA/PPPoE
- Bridge Mode

PPPoE/PPPoA

Connection Setting

6
7
8

Servicename :

Username : waves.iptv.sy

Password : ***wg

Encapsulation : PPPoE LLC

PPP Authentication : AUTO

Bridge Interface : Activated Deactivated

IP Common Options

Connection : Always On (Recommended)
 Connect On-Demand (Close if idle for 0 minutes)
 Connect Manually

TCP MSS Option : TCP MSS(default: 1400) 1400 bytes

IPv4 Address

Default Route : Yes No 9

Get IP Address : Static Dynamic

Static IP Address : 0.0.0.0

IP Subnet Mask : 0.0.0.0

Gateway : 0.0.0.0

TCP MTU Option : TCP MTU(default: 1480) 1480 bytes

NAT : Enable

Dynamic Route : RIP2-B Direction : Both

Multicast : IGMP v2

MAC Clone : Enabled Disabled
00:00:00:00:00:00

10

Advanced

Quick Start

11

Interface Setup

Advanced Setup

Access Management

Maintenance

Status

Help

Firewall

Routing

NAT

QoS

VLAN

ADSL

12

Firewall

Firewall : Enabled Disabled

(WARNING: If you enabled Firewall, the modem can block such attack:Denial of Service, SYN Flooding, Ping of Death, TearDrop...etc)

SPI : Enabled Disabled

(WARNING: If you enabled SPI, all traffics initiated from WAN would be blocked, including DMZ, Virtual Server, and ACL WAN side.)

SAVE

CANCEL

Advanced

Quick Start

Interface Setup

Advanced Setup

Access Management

Maintenance

Status

Help

Firewall

Routing



NAT

QoS

VLAN

ADSL

Routing Table List

#	Dest IP	Mask	Gateway IP	Metric	Device	Use	Edit	Drop
1	185.158.92.2	32	185.158.92.2	1	poe4	0		
2	10.10.0.200	32	10.10.0.200	1	poe0	0		
3	10.1.0.0	24	PVC0	1	poe0	4541487		
4	192.168.1.0	24	192.168.1.1	1	enet0	6675931		
5	default	0	Node5	2	poe4	45585		

13

ADD ROUTE

Advanced

- Quick Start
 - 14 Interface Setup
 - Advanced Setup
 - Access Management
 - Maintenance
 - Status
 - Help
- Firewall | Routing | NAT | QoS | VLAN | ADSL

Static Route

15 Destination IP Address : 10.1.0.0

16 IP Subnet Mask : 255.255.255.0

Gateway IP Address : 0.0.0.0 PVC0 17

18 Metric : 1

Announced in RIP : Yes

protv

19

SAVE DELETE BACK CANCEL

14

Advanced

Quick Start

Interface Setup

Advanced Setup

Access Management

Maintenance

Status

Help

Firewall

Routing

NAT

QoS

VLAN

ADSL

Static Route

16

15 Destination IP Address : 10.237.239.0

IP Subnet Mask : 255.255.255.0

Gateway IP Address : 0.0.0.0

PVC0

17

18 Metric : 1

Announced in RIP : Yes

liketv

19

SAVE

DELETE

BACK

CANCEL