



1

- Wizard
- Internet Setup
- Wireless
- Local Network
- LAN IPv6
- Time and Date
- Logout

SETTING UP YOUR INTERNET

You can set up the Internet connection through either of the two ways: Web-based InternetConnection Setup Wizard; Manual setup

2 For manual setup, you need to have the connection settings provided by your ISP.

INTERNET CONNECTION WIZARD

This wizard assists you to quickly connect the new router to the Internet, through step-by-step instructions. Click the button below to begin.

Setup Wizard

Note: Before launching the wizard, please ensure that you have correctly followed the steps outlined in the Quick Installation Guide corresponds to the router.



DSL-2750U //

SETUP

ADVANCED

MANAGEMENT

STATUS

HELP

Wizard

Internet Setup

Wireless

Local Network

LAN IPv6

Time and Date

Logout

INTERNET SETUP

Choose "Add", "Edit", or "Delete" to configure WAN interfaces.

If you want to change WAN access type, you can click on "Ethernet" or "DSL".

note : If you select the WAN access type is "Ethernet", Please send line to LAN4 port!

WAN Access Type : ☐ Ethernet ☒ DSL

DSL SETUP

	VPI/VCI	VLAN ID	ENCAP	Service Name	Protocol	State	Status	Backup3G	Action
☒	8/35	0	LLC	PVC:8/35	PPPoE	1	Connected	1	Disconnect

ETHERNET SETUP

	VLAN ID	Service Name	Protocol	State	Status	Action
--	---------	--------------	----------	-------	--------	--------

3 [Add](#) [Edit](#) [Delete](#)

BROADBAND

- Local Network
- LAN IPv6
- Time and Date
- Logout

4

VPI : 0 (0-255)

VCI : 32 (32-65535)

Service Category : UBR With PCR

Peak Cell Rate : 0 (cells/s)

Sustainable Cell Rate : 0 (cells/s)

Maximum Burst Size : 0 (cells)

CONNECTION TYPE

5

Protocol : PPP over Ethernet (PP

Encapsulation Mode : LLC

802.1Q VLAN ID : 0 (0 = disable, 1 - 4094)

Priority : 0 (0 - 7)

Firewall Enable : ☒

IPv4 Enable : ☒

IPv6 Enable : ☐

☐ Enable Proxy Arp

PPP USERNAME AND PASSWORD

PPP Username : @waves

PPP Password : *****wg

Confirm PPP Password : *****wg

Authentication Method : AUTO

WAN Service Type : Internet

Dial-up mode : AlwaysOn

ADSL Router - Google Chrome



DSL-2750U //

SETUP

ADVANCED

MANAGEMENT

STATUS

HELP

Wizard

Internet Setup

Wireless

Local Network

LAN IPv6

Time and Date

Logout

INTERNET SETUP

Choose "Add", "Edit", or "Delete" to configure WAN interfaces.

If you want to change WAN access type, you can click on "Ethernet" or "DSL".

note : If you select the WAN access type is "Ethernet", Please send line to LAN4 port!

WAN Access Type : ☐ Ethernet ☒ DSL

DSL SETUP

	VPI/VCI	VLAN ID	ENCAP	Service Name	Protocol	State	Status	Backup3G	Action
☒	8/35	0	LLC	PVC:8/35	PPPoE	1	Connected	1	Disconnect
☐	0/32	0	LLC	PVC:0/32	PPPoE	1	Disconnected	1	Connect

ETHERNET SETUP

	VLAN ID	Service Name	Protocol	State	Status	Action
--	---------	--------------	----------	-------	--------	--------

6

[Add](#)[Edit](#)[Delete](#)

BROADBAND

Dial-up mode : AlwaysOn

ADSL Router - Google Chrome

DSL-2750U	SETUP	ADVANCED	MANAGEMENT	STATUS	HELP
Wizard	INTERNET SETUP				
Internet Setup	In this page, you can configure an ATM PVC identifier (VPI and VCI) and select a service category.				
Wireless	ATM PVC CONFIGURATION				
Local Network	7 VPI : 0 (0-255) VCI : 32 (32-65535) Service Category : UBR With PCR Peak Cell Rate : 0 (cells/s) Sustainable Cell Rate : 0 (cells/s) Maximum Burst Size : 0 (cells)				
LAN IPv6	CONNECTION TYPE				
Time and Date	8 Protocol : Bridging Encapsulation Mode : LLC 802.1Q VLAN ID : 0 (0 = disable, 1 - 4094) Priority : 0 (0 - 7) Firewall Enable : ☒ ☐ Enable Proxy Arp				
Logout	9 Enable Bridge Service : ☒ Service Name : br_0_32_0_3 Apply Cancel				

ADSL Router - Google Chrome



10

Wizard

Internet Setup

Wireless

Local Network

LAN IPv6

Time and Date

Logout

INTERNET SETUP

Choose "Add", "Edit", or "Delete" to configure WAN interfaces.

If you want to change WAN access type, you can click on "Ethernet" or "DSL".

note : If you select the WAN access type is "Ethernet", Please send line to LAN4 port!

WAN Access Type : ☐ Ethernet ☒ DSL

DSL SETUP

	VPI/VCID	VLAN ID	ENCAP	Service Name	Protocol	State	Status	Backup3G	Action
☒	0/32	0	LLC	PVC:0/32	Bridge	1	Connected	-	-
☐	8/35	0	LLC	PVC:8/35	PPPoE	1	Connected	1	Disconnect
☐	0/32	0	LLC	PVC:0/32	PPPoE	1	Disconnected	1	Connect

ETHERNET SETUP

VLAN ID	Service Name	Protocol	State	Status	Action
---------	--------------	----------	-------	--------	--------

Add Edit Delete

BROADBAND

DSL-2750U

SETUP

ADVANCED

MANAGEMENT

STATUS

HELP

DSL-2750U

SETUP

ADVANCED

MANAGEMENT

STATUS

HELP

Advanced Wireless

Port Forwarding

DMZ

SAMBA

3G Configuration

Parental Control

Filtering Options

QoS Configuration

Firewall Settings

DNS

Dynamic DNS

Network Tools

Routing

Schedules

NAT

FTPD Setting

FTPD Account

IP Tunnel

Logout

ADVANCED WIRELESS -- ADVANCED SETTINGS

You can configure advanced features of the wireless LAN interface.

Advanced Settings

ADVANCED WIRELESS -- MAC FILTERING

You can configure wireless firewall by denying or allowing designated MAC addresses.

MAC Filtering

ADVANCED WIRELESS -- SECURITY SETTINGS

You can configure security features of the wireless LAN interface.

Security Settings

ADVANCED WIRELESS -- WPS SETTING

You can configure wireless WPS.

WPS Setting

Static Routing

IPv6 Static Route

Policy Route

Default Gateway

RIP

RIPng

11

ADSL Router - Google Chrome

STATIC ROUTE

Enter the destination network address, subnet mask, gateway, metric, AND/OR available WAN/LAN interface. Then, click "Apply" to add the entry to the routing table.

A maximum 30 entries can be configured.

ROUTING -- STATIC ROUTE

Destination	Subnet Mask	Gateway	Interface	Metric
-------------	-------------	---------	-----------	--------

Add Edit Delete

STATIC ROUTE ADD

Destination Network Address : 10.1.0.0
Subnet Mask : 255.255.255.0
Use Interface : PVC:0/32
Metric : 1

ASP-PROTV

Apply cancel

- Advanced Wireless
- Port Forwarding
- DMZ
- SAMBA
- 3G Configuration
- Parental Control
- Filtering Options
- QoS Configuration
- Firewall Settings
- DNS
- Dynamic DNS
- Network Tools
- Routing
- Schedules
- NAT
- FTPD Setting
- FTPD Account
- IP Tunnel
- Logout

STATIC ROUTE

Enter the destination network address, subnet mask, gateway, metric,AND/OR available WAN/LAN interface. Then, click "Apply" to add the entry to the routing table.

A maximum 30 entries can be configured.

ROUTING -- STATIC ROUTE

Destination	Subnet Mask	Gateway	Interface	Metric
Add Edit Delete				

STATIC ROUTE ADD

Destination Network Address : 10.237.239.0

Subnet Mask : 255.255.255.0

Use Interface : PVC:0/32

Metric : 1

Applycancel

ASP-LIKETV

